

MSA Cable Temporary Horizontal Lifeline



Technical Data Sheet



PART NUMBER	10219297
DESCRIPTION	MSA Cable Temporary Horizontal Lifeline, 18,3 m (60 ft.)
ANCHOR STRAPS INCLUDED	No
LIFELINE LENGTH	1,5-18,3 m (5-60 ft)
LIFELINE CONSTRUCTION	6 × 19, 8 mm (5/16 in), fiber core
LIFELINE MATERIAL	Galvanized Steel Cable
CAPACITY	59-141 Kg (30-310 lb)
INSTALL TYPE	Temporary/Portable
TURNBUCKLE	Zinc plated Carbon Steel
THREADED SHAFTS	Stainless Steel, PTFE Coating
ENERGY ABSORBER COVER	Polycarbonate with overmolded rubber
CARABINERS	Triple lock aluminum 30 kN minimum breaking strength
USERS	Max 2 users
SPAN TYPE	Single span only
PHYSICAL WEIGHT	7,9 Kg (17,4 lb)
RFID	Yes
COMPATIBILITY	MSA Cable Temporary Horizontal Lifeline System is designed for use with compatible MSA components, connectors, and subsystems.
STANDARDS	EN 795:2012 Type C, CEN/TS 16415:2013

Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice. MSA is a registered trademark of MSA Technology, LLC in the US, Europe, and other Countries. For all other trademarks visit <https://us.msasafety.com/Trademarks>.

MSA har verksamhet i över 40 länder över hela världen. För att hitta ett MSA-kontor nära dig, besök [MSAsafety.com/offices](https://us.msasafety.com/offices).